



nr. tabeli 2

Rodzaj podprór		Podpory state											
Typ		I				II				III			
DN		32÷50	65÷80	100÷125	150	32÷80	100÷125	150	32÷50	65÷80	100÷125	150	
Konstrukcje na ścianach mururowanych	L (cm)	65	65	80	95	30	40	40	68	68	68	68	150
	L ₁ (cm)	85	85	100	105 115	50	60	60	88	88	88	88	88
	Masa stali (kg)	7,0	10,9	20,8	37,0	2,5	6,2	8,5	5,2	8,3	11,8	18,2	18,2
	V betonu (m ³)	0,01	0,01	0,01	0,03	0,01	0,01	0,01	0,01	0,01	0,01	0,01	0,01
	Symbol	PM-I/50	PM-I/80	PM-I/125	PM-I/150	PM-II/80	PM-II/125	PM-II/150	PM-III/50	PM-III/80	PM-III/125	PM-III/150	PM-III/150
Konstrukcje na ścianach żelazobetonowych	L (cm)	63	63	78	83	31	40	40	63	63	63	68	68
	Masa stali (kg)	11,3	13,2	23,3	37,3	4,4	10,7	10,7	8,1	9,2	29,3 45,8	21,0	21,0
	Symbol	PB-I/50	PB-I/80	PB-I/125	PB-I/150	PB-II/80	PB-II/125	PB-II/150	PB-III/50	PB-III/80	PB-III/125	PB-III/150	PB-III/150

Handwritten signature